



TECHNICAL SPECIFICATION

MC Connect HTTP

Document version 2.15

Basic information

Identification	
Name:	Technical specification MC Connect HTTP
Document version:	2.15
Create date:	2005-06-07
Last update date:	2021-02-16
Template version:	SAB_Uzivatelska_prirucka_20210101.docx
State:	production
Limitations:	none

Purpose of this document

This document covers complete specification of bi-directional proprietary HTTP-based protocol for transport of short messages (SMS) and delivery reports.

Features – content

1. Mobile originated message: COMVERGA to Client (MO-AT) push
2. Application originated message: Client to COMVERGA (AO-MT)
3. MT Billing
4. Delivery reports

Copyright © 2008-2021 COMVERGA a.s. All rights reserved.

This document is protected by copyright. All rights, including those of translation, of reprinting and of copying using photo-mechanical or electronic means, are reserved. Protected trademarks, registered names etc., are not identified in the text. The absence of such a designation does not mean that a name is free of copyright within the context of the trade and brand name legislation. The names of persons and companies which are used as examples are purely fictitious.

Limitation of liability

The information contained in this document has been carefully checked, and as such may be considered to be reliable. However, we cannot undertake to guarantee that information specified in this document is without error. In particular, no commitment has been made as to whether the products which have been described are or are not suitable for particular purposes.

COMVERGA reserves the right to make changes to the products and product information. COMVERGA does not accept any further liability which results from the use of the products here described. The issuing of this document does not constitute any kind of license to use the products detailed, neither from COMVERGA nor from third parties.

COMVERGA a.s.
Starokolínská 306, Prague
CZ-19016, Czech Republic

Technical support:
tel +420 234 493 130
E-mail support@comverga.com

History of changes

Date	Version	Author	Description
2005-06-07	1.0		Document created
2009-09-17	1.6		Delivery reports
2009-09-18	1.7		UDH and concatenated messages
2009-10-05	1.8		Delivery reports: StatusCode adjustment. Document formatting
2009-10-14	1.9		MTBSS (MT billing subscription service) API description.
2010-01-04	2.01		MT_VValidityPeriod
2010-01-15	2.02		The „pull“ interface for MO-AT
2010-02-15	2.03		Link supervision – connection testing; document re-formatting for export
2010-03-31	2.04		Detailed examples in „Application originated message (AO-MT)“ section
2010-04-21	2.05		Reports – new statuscode „11“ (no report from PLMN operator in 3 days)
2010-10-07	2.07		MT billing (MT_Billing_Bill) default value changed from 0 to 1
2010-11-24	2.08		Added optional OpID to http response format
2010-12-02	2.09		Changed „comverga sends http GET/POST“ to „comverga sends http GET“ because POST is never used; removing „method=GET“ configuration from etc/clients/*.ini
2011-03-25	2.10		Removed section MO-AT pull
2012-01-02	2.11		DN_Creator_Name and DN_RefID no longer in AO delivery reports
2012-04-06	2.12		HTTPS is required on client side
2019-10-22	2.13	MSp	Company logo update
2020-08-20	2.14	JBr	Added optional input parameter MT_Priority
2021-02-16	2.15	MSp	Company logo and name update
2025-11-20	2.15	MSp	Footer update – Company information
2026-08-07	2.15	MKr	Document update - Comverga instead Materna

1. Mobile originated message: COMVERGA to Client (MO-AT)

For each one MO-AT message, MMR creates a HTTPS GET request (insecure HTTP is not supported). Short message is being „encoded“ into URI string. The request is being „sent“ to client's application with login and password via HTTP basic authentication.

Parameters description:

Parameter	Description	Example
MO_MessageID	Unique message ID assigned by MMR. You have to check for duplicates!	EurotelCZ.M2MPSMS_0001a365
MO_Source	Source number (MSISDN) of the message.	+420602123456
MO_Destination	Destination number (shortcode) of the message.	9003030
MO_Timestamp	Message timestamp (SCTS). 14-digit format (YYYYMMDDhhmmss).	20120229235012
MO_Data	<u>Type=SMS, SubType=Text</u> Message text , UTF8 string, URL-encoded <u>Type=SMS, SubType=Binary</u> Data payload , hexdump <u>Type=MMS</u> <i>Not defined</i>	UTF8 string „Přiliš%20žluťoučký%20kůr“ Hexdump: “00fc01AA” represents 4 octets 0x00, 0xfc, 0x01 and 0xaa
MO_Type	Type of the message SMS – text message MMS – multimedia message	SMS
MO_SubType	Format of MO_Data - 'Text' or 'Binary'	Text
MO_UDH	User Data Header , hexdump Contains binary sequence as hexdump.	The string „050003010201“ indicates 6 octets of UDH (0x05 0x00 0x03 0x01 0x02 0x01).
MO_PID	Protocol ID (integer, 0 ... 255) Protocol identification according to GSM 03.40.	215

Example

```
https://content-provider.eu/sms/receiver?MO_MessageID=EurotelCZ.M2MPSMS_0001a365&MO_Source=%2B420602123456&MO_Destination=9003030&MO_Timestamp=20120229235012&MO_Type=SMS&MO_SubType=Text&MO_Data=This+is+a+test+message
```

Client application responds with HTTP code "200", Content-Type: text/plain" and body in form:

- **OK** *client confirms receiving of the message*
- or
- **OK;warning - duplicate** *client confirms with warning from duplicity check*
- or
- **OK;<parameters>** *client confirms & sends a reply message directly¹*

When the body text begins with "OK", message is considered as accepted, otherwise will be re-sent in a short interval (seconds).

When the body text begins with "OK;<parameters>", and at least MT_Data element is present, message is considered as accepted and direct reply (MT message) is sent. See „Direct Replies“ below.

Duplicity check – please read this paragraph carefully

The possibility of duplicate delivery of a message is natural phenomenon of HTTP-based message transport². The only way to cope with this problem is application logic. Please consider having such a piece of logic in your SMS transport implementation. Thank you.

There is unique identification of each message you receive: MO_MessageID. It's assigned by MMR (length 8 to 60 characters, character set [A-Za-z0-9_]). Client must store MessageID of each received message/report in some storage (say received_id_list) for future duplicity checks. When receiving messages, before pushing them to permanent storage or processing them, its MessageID must be checked against received_id_list.

If MessageID of received message **is found** in received_id_list, it's duplicate. Client application must

1. ignore the message (don't store to storage, don't push it to processing), but
2. send positive acknowledge (OK³), as when message is accepted,
3. send the same direct-reply as before (when using direct replies).

If MessageID of received message **is not found** in received_id_list, there is no problem. Client application must

1. push message to its permanent storage and/or processing code,
2. send positive/negative acknowledge (OK or Error) – depending of result of storage/processing.

Link supervision – connection testing

This (push) interface is regularly tested from COMVERGA side. In case there is no MO traffic for at least 30 minutes, COMVERGA may send the „enquire_link“ request to check whether the client's HTTP server is up. The http request contains one parameter:

Parameter	Description	Example
enquire_link	regular connection testing	<i>no value</i>

-
- 1 there is a possibility to reply offline, see further
 - 2 Why? Imagine this: Client sends message to server, server receives it, sends positive response, but the response is lost. Server has the message received successfully. Client sees no response – times out. Client considers that message delivery failed and re-send the same message. Server receives the same message again.
 - 3 with „warning – duplicate“ information

and no SMS-related parameters (MO_*).

The application is required to send at least 200 OK (on http level). Content (response) may contain anything, or nothing. After client's HTTP server sends HTTP 200 OK, the link is considered up.

Example

`https://content-provider.eu/sms/receiver?enquire_link`

Response:

HTTP/1.1 200 OK

Direct Replies

*Warning: Direct reply **may not** be used for statefull applications. The HTTP Response, as a bearer of reply message, doesn't guarantee successfull delivery⁴. Use with caution! Contact COMVERGA support if you are not sure. Use indirect replies (see „application originated message“ below) if you are still not sure.*

Parameters are in form of http GET request. The Direct Reply may contain following parameters:

Parameter	M/O	Description	Example
MT_Data	M	message text/data	Hello%20world.
MT_Type	O	type, 'SMS' (default) or 'MMS'	SMS
MT_SubType	O	subtype, 'Text' (default) or 'Binary'	Text
MT_DCS	O	data coding scheme ⁵	245
MT_ReportRequest	O	0 ... delivery report not requested (default) 1 ... delivery report requested	0
MT_UDH	O	User data header	0605040B8423F0
MT_Billing_Bill	O	0 ... set zero MT-billing code (subscriber receives message for free) 1 ... set non-zero MT-billing code (subscriber is charged while receiving the message) (default) <i>(applicable in selected countries/operators only)</i>	1

(M)andatory, (O)ptional

Example: (MT_Type=SMS&MT_SubType=Text&MT_Data=This+is+a+reply+message)

See „Application originated message“ for details.

⁴ The retry-on-timeout mechanism on MMR side may trigger duplicate messages when http response is lost

⁵ MT_DCS - if you use characters from ASCII (GSM7), don't use this parameter in AO message

Client-side implementation example

The sample PHP script (receiver.php) for receiving MO messages looks like:

```
<?php
/*
 * © COMVERGA a.s. 2005-2010
 * Sample PHP script for receiving MO-AT SMS for "SMS connect" service (with no direct reply)
 *
 * -- NOT FOR PRODUCTION USE -- This is an example
 */

header('Content-type: text/plain');

/* (1) Client must check for repeated message - duplicity check */
if ( "$_REQUEST[MO_MessageID] found in my_received_id_list, 30 days back" )
{
    echo "OK;warning - duplicate\n";    /* confirm but don't process the message */
}
else
{
    /* (2) Client should store the message into a file, database or other permanent storage */
    if ( "message stored successfully" )
    {
        echo "OK\n";                    /* confirmation to MMR */
    }
    else
    {
        echo "Error - <some error description or whatever>\n";
        /* MMR will re-send the same message */
    }
}

?>

== Received message ==
Identification: [<?= $_REQUEST[MO_MessageID] ?>]
Sender: [<?= $_REQUEST[MO_Source] ?>]
Receiver: [<?= $_REQUEST[MO_Destination] ?>]
Message body: [<?= $_REQUEST[MO_Data] ?>]

== SMS dump ==
<?php var_export( $_REQUEST ) ?>
```

Connection parameters (bi-directional push interface)

The per-client, per-service connection parameters:

Item	Example value	Assigned by
MO-AT		
URL (MMR side)	https://content-provider.eu/sms/receive/	Client
http-basic username	Comverga	Client
http-basic password	Kxxyt53jSDr.44	Client
AO-MT		
URL (MMR side)	https://sms.comverga.com/mmr/mo_pull	COMVERGA
http-basic username	ServiceXyz90030	COMVERGA
http-basic password	jeCsf29976	COMVERGA

MMR crocks: mt routing: type=http2; FCGI: send

2. Application originated message: Client to COMVERGA (AO-MT)

Sending bulk SMS/Replying to Premium SMS

Client application sends messages via http request GET, authenticating itself with login and password via HTTP basic authentication.

For each one Application Originated message, client application creates a HTTP(S) GET request. Short message is being „encoded“ into URI string. The request is being „sent“ to MMR with login and password via HTTP basic authentication.

HTTP request elements

Parameter	M/O	Description	Example
MT_Source	O	Source number (shortcode) of the message.	9003030
MT_Destination	M	Destination number (MSISDN) of the message. See also: „OP:<OpID>“ in response-line.	+420602123456
MT_Data	M	<u>Type=SMS, SubType=Text</u> Message text , UTF8 string, URL-encoded <u>Type=SMS, SubType=Binary</u> Data payload , hexdump <u>Type=MMS</u> <i>Not defined</i>	UTF8 string „Přiliš%20žlutoučký%20kůň“ Hexdump: “00fc01AA” represents 4 octets 0x00, 0xfc, 0x01 and 0xaa
MT_Type	O	Type of the message SMS – text message (default) MMS – multimedia message	SMS
MT_SubType	O	Format of MT_Data - 'Text' (default) or 'Binary'	Text
MT_RefID	O	MO_MessageID value of related MO message (required for MT billing services)	EurotelCZ.M2MPSMS_0001a365
MT_DCS	O	data coding scheme ⁶	245
MT_ReportRequest	O	0 ... delivery report not requested (default) 1 ... delivery report requested	0
MT_UDH	O	User Data Header , hexdump Contains binary sequence as hexdump. Useful for concatenated messages.	0605040B8423F0
MT_Billing_Bill	O	0 ... set zero MT-billing code (subscriber receives message for free) 1 ... set non-zero MT-billing code (subscriber is charged while receiving the message) (default) <i>(applicable in selected countries/operators only)</i>	1

⁶ MT_DCS - if you use characters from ASCII (GSM7), don't use this parameter in AO message

Parameter	M/O	Description	Example
MT_VValidityPeriod	O	The <i>MT_VValidityPeriod</i> indicates the expiration time, after which the SMSC stops delivery attempts on message. Such a message will be discarded, when not (yet) delivered at VP time. The corresponding (EXPIRED) delivery report is returned back. The <i>MT_VValidityPeriod</i> is specified as absolute 14-digit timestamp (YYYYMMDDhhmmss), local time. There are limitations: • minimum: VP must be at least 15 minutes in future. If not, MMR will adjust the VP to now+15min and the warning is returned. • maximum: VP must not exceed 7 days in future. If the specified VP exceeds now+7d, it's adjusted by MMR and the warning is returned.	20150228090807
MT_Priority	O	Relative priority of the message. Allowed values: • low • normal (default) • high	high

(M)andatory, (O)ptional

HTTP response format

MC system responds with HTTP code "200", Content-Type: text/plain" and body. The very first line of response body is defined; any additional line(s) should be ignored.

In the response-line, one of 3 replies may occur:

- **OK;<MC_MessageID>;<RecD>;<OP:<OpID>];optional human-readable text]**
 - OK ... fixed value (indicates success).
 - MC_MessageID ... unique message identifier assigned by MMR (length 8 to 60 characters, character set [A-Za-z0-9_]).
 - RecD ... recommended minimum delay before submitting next message (milliseconds); by obeying this recommended delay, you won't reach the 'THROTTLING-ACTIVE' (see below).
 - OpID ... numeric identification of destination operator (1-65535) as determined from MT_Destination by MMR's routing table and NP database; presence of this element is configurable per client; the value is country- and installation-specific.
- **REJECT;<reason of rejection>**
 - Message rejected permanently by MMR (protocol error/malformed message); do not try to re-send such a message. See <reason of rejection> for details.
- **ERROR;<error description>**
 - MMR would like to accept such a message. Unfortunately, there was a temporary indisposed conditions causing the message was not stored. Please re-send the same message again. Please wait at least 30 seconds before.

- **THROTTLING-ACTIVE;<RecD>[;optinal human-readable text]**
 - Message not accepted – maximum throughput exceeded. Please re-send the same message again. You should wait spacificed amount of milliseconds (see RecD) before re-sending, otherwise the message will be rejected again.
 - RecD ... recommended minimum delay before re-submitting the same message (milliseconds).

Example – simple MT message

`https://mmr.comverga.com/mmr/send?MT_Source=9003030&MT_Destination=%2B420602123456&MT_Type=SMS&MT_SubType=Text&MT_Data=This+is+a+test+message:%C5%BDlu%C5%A5ou%C4%8Dk%C3%BD%20k%C5%AF%C5%88%20ti%C5%A1e%20%C5%99eht%C3%A1%20@.-,`

Explanation: this http request represents text message „COMVERGA testing message:Žluťoučký kůň tíše řehťá @.-,“ from shortcode 9003030 to MSISDN +420602123456.

Example – response

OK;HbxPSMS_00000a84;470ms;OP:208

*Explanation: this response confirms that the above message was accepted with identification **HbxPSMS_00000a84** and recommended minimum delay before submitting next message is **470** milliseconds. The message's destination number (**+420602123456**) is national operator number **208**.*

Connection parameters (bi-directional push interface)

The per-client, per-service connection parameters:

Item	Example value	Assigned by
MO-AT		
URL (MMR side)	<code>https://content-provider.eu/sms/receive/</code>	Client
http-basic username	Comverga	Client
http-basic password	Kxxyt53jSDr.44	Client
AO-MT		
URL (MMR side)	<code>https://sms.comverga.com/mmr/mo_pull</code>	COMVERGA
http-basic username	ServiceXyz90030	COMVERGA
http-basic password	jeCsf29976	COMVERGA

MT_UDH

- MT_UDH must contain binary-as-hexdump. The string „050003010201“ indicates 6 octets of UDH (0x05 0x00 0x03 0x01 0x02 0x01).

Concatenated messages

To send concatenated (long) SMS messages you can use parameter MT_UDH:

MT_UDH must be in this format: 050003DDXXYY, where:

- 050003 is fixed part
- DD: 01-FF, CSMS reference number, must be same for all the SMS parts in the CSMS
- XX: 01-FF, total number of parts concatenated message.

- YY: 01-FF, this part's number in the sequence

For sending long (concatenated) messages, you can set parameter MT_UDH and split long message by 153 characters. Example: message with 200 characters will be splitted to the two parts, one with 153 characters, second with 47 characters.

Example – concatenated (long) MT message

Part 1 of 2

Request (client → COMVERGA)

`https://mmr.comverga.com/mmr/send?MT_Source=%2B420234567890&MT_Destination=%2B494617123456&MT_Type=SMS&MT_SubType=Text&MT_UDH=050003010201&MT_Data=This+is+a+test+message+first+part+with+153+characters.....`

Response (COMVERGA → client)

MC system responds with HTTP code "200", Content-Type: text/plain" and body in form:

`OK;ExampleService90030xx_00de5012;4978ms`

Part 2 of 2

Request (client → COMVERGA)

`https://mmr.comverga.com/mmr/send?MT_Source=%2B420234567890&MT_Destination=%2B494617123456&MT_Type=SMS&MT_SubType=Text&MT_UDH=050003010202&MT_Data=This+is+a+test+message+second+part`

Response (COMVERGA → client)

MC system responds with HTTP code "200", Content-Type: text/plain" and body in form:

`OK;ExampleService90030xx_00de5013;9971ms`

- MC_MessageID for both messages will be different
- Each part of concatenated message will be billed as single message

3. MT Billing

There are two main branches of billing style on the field of Premium Short Message Services.

- MO billing: mobile subscriber is charged while sending MO. Mobile subscriber receives MT for free. This scheme is considered as default for Premium SMS.
- MT billing: mobile subscriber sends MO with no extra fee⁷. Mobile subscriber is charged while receiving MT.

The MT billing consists of two different use cases.

1. One-shot service: Mobile subscriber sends MO; low amount (one, typ. up to 5) MT messages follows.
2. Subscription service: Mobile subscriber orders the service, and confirms the subscription. Limited amount of MT (charged) messages is sent to subscriber within unlimited time frame.

Note for Czech Republic: Whole process of ordering service billed via MT messages and delivering MT billed messages must fulfill requirements listed in APSMS codex (normative for all local mobile operators and content

⁷ the MO message is billed as ordinary on-net message according to subscriber's tariff

providers). See <http://platmobilem.cz/>, **Kodex Premium SMS** [english].

SMS flow description – one-shot service

Client sends MT billed messages via MMR. Messages should be sent as ordinary MT messages (see „*Application originated message: Client to COMVERGA*“), with some exceptions:

- The source number (MT_Source) should be used consistently according to the price.
 - For billed premium MT messages, use 8-digit shortcode as MT_Source in form 90xyyzzz; zzz is end-price incl. VAT in CZK (90030005 → 5,00 CZK, 90230095 → 95,00 CZK)
 - For non-billed (non-premium) MT messages, use 5-digit shortcode as MT_Source.
- You should always request a delivery report (MT_ReportRequest=1) to know delivery status of message. Successful submit of billed MT message does not guarantee that end-user is really billed. The message may be encountered as billed only after positive delivery report (with StatusCode=0; see below).

SMS flow description – subscription service, Czech Republic

The service providing entity (client) will need a “table of subscribed numbers”. COMVERGA recommends following layout of the table:

Msisdn	Reference
<i>MSISDN of subscribed end-user. Copy of MO_Source from “START” command.</i>	<i>Unique ID of subscription. Copy of MO_MessageID</i>

Example of “table of subscribed numbers”

Msisdn	Reference
+420601234567	GsmCZ.M2M_0001baaa
+420601234599	GsmCZ.M2M_000203dc
...	...

- on new subscription (mtbill_code=START), client inserts the record into table of subscribed numbers
 - in case of duplicity of MSISDN, the “reference” must be updated
- on subscription end (mtbill_code=STOP), client removed the record by MSISDN

Process

1. Enduser sends SMS to a five digit shortcode⁸ serviced by MMR⁹. SMS text begins with a keyword assigned to client. Provider (MC) must allow enduser to set maximum count of MT billed messages (for one service) per day, which he (she) is willing to receive. (This message is not considered as a Premium rate MO SMS. More info in enclosed APSMS codex.)

⁸ Czech Republic

⁹ MT billing subscription service may also be started by http request from client's application (end-user don't have to send 1st MO SMS); see „MTBSS API“ below.

- MMR generates the „challenge“ - MT SMS with description of client's service and direction how to confirm the service order (reply „YES <servicename>“ to start subscription). Text of this message is strictly declared by Codex. This message is free of charge for enduser.
- MMR creates a HTTP GET request to client application, authenticating itself with login and password via HTTP basic authentication, with **info** about client's request. This kind of request will be generated for all MO messages sent to five digit prefix with client's keywords in SMS text.

Parameters description – the INFO command:

Parameter	Description	Example
See „Mobile originated message: COMVERGA to Client“ for common parameters		
MO_SpecialInfo	the fixed string „mtbill_code=info“: informs client about end-user's (not yet confirmed) request	mtbill_code=info

Example:

https://client.com/receive?MO_SpecialInfo=mtbill_code%3Dinfo&MO_Source=%2B420602123456&MO_Destination=90235&MO_Timestamp=20060329235012&MO_Type=SMS&MO_MessageID=GsmCZ.PSMS_0001a365&MO_SubType=Text&MO_Data=Eur10

Client application responds with HTTP code "200", Content-Type: text/plain" and body in form:

OK;

When the body text begins with "OK", message is considered as accepted, otherwise will be resend in a short interval (seconds).

- Enduser sends „confirmation“ - second SMS with the text „ANO¹⁰ <servicename>“, example: „ANO Eur10“, to the same 5-digit shortcode serviced by MMR. By sending this message enduser confirms order of subscription service. From now, client application may send MT billed messages to enduser's MSISDN.

On start of subscription, MMR sends the „START“ command to the client. MMR creates a HTTP GET request to client application, authenticating itself with login and password via HTTP basic authentication. Parameter „MO_SpecialInfo“ will be set to **mt_billcode=START**. By this request MC confirms that client is allowed to send MT billed messages to enduser's MSISDN.

Parameters description – the START command:

Parameter	Description	Example
See „Mobile originated message: COMVERGA to Client“ for common parameters		
MO_SpecialInfo	the fixed string „mtbill_code=START“: informs client about start of subscription of corresponding MSISDN (MO_Source)	mtbill_code=START
MO_RefID	Reference of the started subscription. Used as MT_RefID for MT billed messages.	GsmCZ.EMI_000dd595

10 Yes

Example:

```
https://client.com/receive?MO_SpecialInfo=mtbill_code%3DSTART&MO_Source=%2B420602123456&MO_Destination=90235&MO_Timestamp=20060329235012&MO_Type=SMS&MO_MessageID=MTBA_00010aaa&MO_RefID=GsmCZ.EMI_000dd595&MO_SubType=Text&MO_Data=Ano+eur10
```

Client's application responds with HTTP code "200", Content-Type: text/plain" and body in form:

OK;

Client must store the msisdn (MO_Source) and reference (MO_RefID) in the "table of subscribed numbers". On duplicate MSISDN, the reference must be updated.

3. Client sends MT billed messages via MMR system until the Subscription is stopped. Messages should be sent as ordinary MT messages (see „*Application originated message: Client to COMVERGA*“), with some exceptions:
 - The source number (MT_Source) should be used consistently according to the price. For billed premium MT messages, use 8-digit shortcode as MT_Source.
 - 8-digit shortcode in form 90xyyzzz; zzz is end-price incl. VAT in CZK (90030005 → 5,00 CZK)
 - The MT_RefID must contain the reference string from "table of subscribed numbers".
 - See „Delivery of billed AO-MT messages“ (below) also.
4. Subscription service may be stopped by following means:
 - Enduser sends message with text "STOP", "STOP ALL", "STOP <keyword>".
 - Enduser's LifeTime limit of Service ran out.
 - Three consecutive MT billed messages were not delivered (negative delivery report)

On stop of subscription, MMR sends the „STOP“ command to the client. MMR creates a HTTP GET request to client application, authenticating itself with login and password via HTTP basic authentication. Parameter "MO_SpecialInfo" will be set to **mtbill_code=STOP**. Client application responds with HTTP code "200", Content-Type: text/plain" and body in form: "OK"; Client application must remove the entry (by MSISDN) from table of subscribed numbers. After this event no MT billed SMS will be delivered to enduser's MSISDN.

Parameters description – the STOP command:

Parameter	Description	Example
See „ <i>Mobile originated message: COMVERGA to Client</i> “ for common parameters		
MO_SpecialInfo	the fixed string " mtbill_code=STOP ": informs client about end of subscription of corresponding MSISDN (MO_Source)	mtbill_code=STOP

Example:

```
https://client.com/receive?MO_SpecialInfo=mtbill_code%3DSTOP&MO_Source=%2B420602123456&MO_Destination=90235&MO_Timestamp=20060329235012&MO_Type=SMS&MO_MessageID=GsmCZ.M2M_0001baaa&MO_RefID=GsmCZ.EMI_000dd595&MO_SubType=Text&MO_Data=
```

=LiteTimeLimit+ran+out

Now, the subscription for +420602123456 (Reference GsmCZ.EMI_000dd595) ends.

Delivery of billed AO-MT messages

Note: Successfull submit of billed MT message does not guarantee that end-user is really billed. The message may be encountered as billed only after positive delivery report (with StatusCode=0; see below).

Each billed (premium) MT SMS from client will be internally authorized by MMR (subscription service).

If MT billed SMS pass the authorization:

MC system creates a HTTP GET request to client application, authenticating itself with login and password via HTTP basic authentication. Parameter "MO_SpecialInfo" will be set to [mt_billcode=ACK](#). Client application responds with HTTP code "200", Content-Type: text/plain" and body in form "OK".

If MT billed SMS does not pass the authorization:

MC system creates a HTTP GET request to client application, authenticating itself with login and password via HTTP basic authentication. Param "MO_SpecialInfo" will set to [mt_billcode=NACK](#). Client application responds with HTTP code "200", Content-Type: text/plain" and body in form "OK".

MTBSS (MT billing subscription service) API description

Client-to-server specification:

Initialization (order) of subscription service via HTTP request:

1. Client's application gets MSISDN of end-user (via web interface etc.)
2. Client's application sends uHTTP request to COMVERGA application with username+password:
 - `http://servicename:password@comverga-server/mmr-mtbss-api/mtbss-api?arguments`
3. COMVERGA application sends HTTP response of type text/plain
 - a. MTBSS:OK;refId=<reference_string>
 - message accepted
 - b. MTBSS:ERROR;<error description>
 - mesage rejected
4. Client's application should handle HTTP-level timeout and/or application error (MTBSS:ERROR) and re-try after configurable amount of time (minimum 120s)

Argument	Value type	Example
Login	per-client	FooBarSubscription25CZK
Password	per-client	big3cret
sourceNumber	dynamic (from web-input)	+420722011456
destinationNumer	per-service	90030
messageText	per-service	FOOBAR

Examples:

`http://FooBarSubscription25CZK:big3cret@comverga-server/mmr-mtbss-api/service-`

start?messageText=FOOBAR&destinationNumer=90030&sourceNumber=%2B420722011456

http://BadooSubscription90030CZK30:big3cret@comverga-server/mmr-mtbss-api/service-start?messageText=BADOO&destinationNumer=90030&sourceNumber=%2B420722011456

4. Delivery reports

Sending delivery reports from COMVERGA message router to the client's application

The delivery reports are related to AO-MT messages. Delivery report informs asynchronously whether (when) MT message was (was not) delivered to the mobile station. Please check with your COMVERGA contact person whether you have delivery reports active on your connection.

One MT message may trigger several delivery reports. There may be some intermediate reports; there is exactly one final report.

Note: Client's application should request the delivery report with MT_ReportRequest=1 parameter while sending AO-MT message.

MC system creates a HTTP GET request to client application, authenticating itself with login and password via HTTP basic authentication.

Parameters description:

Parameter	Presence	Description
DN_MessageID	M	identification of AO message related to this delivery report
DN_Source	O	source number, ie. '+420602123456' (copy of MT_Destination from AO message)
DN_Destination	O	destination number, ie. '9003030' (copy of MT_Source from AO message)
DN_StatusCode	M	Result of delivery
DN_StatusText	O	Human-readable description of message status
DN_Timestamp	M	Timestamp of message status

presence: (M)andatory, (O)ptional

Result of delivery (DN_StatusCode) - overview

DN_StatusCode	Description
-128 ... -1	intermediate status (additional delivery report will follow)
0	final status; message was delivered at <i>DN_Timestamp</i>
1 ... 9	final status; message was not delivered
10...127	final status; delivery status is not known

Result of delivery (DN_StatusCode) - details

DN_StatusCode	Final	Description (message was ...)
-3	n	accepted by PLMN operator (used for MT-billing)
-2	n	accepted by PLMN operator's subsystem on transport-level
-1	n	<i>reserved for internal use</i>
0	y	delivered to mobile station
1	y	not delivered
2	y	rejected by PLMN operator (used for MT-billing)
3	y	expired on SMSC
4	y	rejected by MMR/MTBA (used for MT-billing)
10	y	accepted by PLMN operator on transport-level (not real relivry report)
11	y	expired – no report from PLMN operator within three ¹¹ days

Examples – successfull deliveries

```

DN_StatusCode      0
DN_StatusText      Message delivered
DN_Timestamp       20090730140447
DN_MessageID       ClientACCF_001a9377
DN_Source          +420736302320
DN_Destination      +420737000111
  
```

Message from 736302320 (virtualSC number) to (+420)737000111 has been delivered at 14:04:47.

```

DN_StatusCode      0
DN_StatusText      Zprava byla dorucena - ISUC_005 - Message delivered
DN_Timestamp       20090730140346
DN_MessageID       ClientXPPS_001a9372
  
```

Message ClientXPPS_001a9372 has been delivered at 14:03:46 ¹².

```

DN_StatusCode      0
DN_StatusText      SUCCESSFUL_DELIVERY
DN_Timestamp       20091005120225
DN_MessageID       XdcSubscription90030CZK30_000169ba
DN_Source          90030030
DN_Destination      +420775773773
  
```

Message from 90030030¹³ to (+420)775773773 has been delivered at 12:02:25.

Examples – failed deliveries

```

DN_StatusCode      1
DN_StatusText      Message delivery failed with error code 000
DN_Timestamp       20090730130003
  
```

¹¹ The timeout (3 days) may vary per installation, per service

¹² the source and destination number elements are optional

¹³ MT billing, price level 30,00 CZK

DN_MessageID ClientXPPS_001a8f28
DN_Source +420736302320
DN_Destination +420732000000

Message id ClientXPPS_0a18f28 has not been delivered; see DN_StatusText for operator-specific cause.

DN_StatusCode 1
DN_StatusText Zprava nebyla dorucena - ISUC_006 - Message delivery failed
DN_Timestamp 20090730125101
DN_MessageID ClientXPPS_001a92f0
DN_Source 1991023

Message id ClientXPPS_0a18f28 has not been delivered; see DN_StatusText for operator-specific cause.

DN_StatusCode 1
DN_StatusText No Connector found for Source [] and Destination
[+42076583700]
DN_Timestamp 20090730124939
DN_MessageID ClientXPPS_001a92a0
DN_Source
DN_Destination +42072583700

Message id ClientXPPS_0a18f28 has not been delivered; dropped by MMR because of missing A-number (empty DN_Source).

DN_StatusCode 2
DN_StatusText rejected on transport-level (Connector.SMPP rejected): (Code
64) MSISDN has not enough credit.
DN_Timestamp 20091001112233
DN_MessageID AqSubscription90030CZK30_0001696d

Message id AqSubscription90030CZK30_0001696d (MT billing) has not been delivered; rejected by operator – pre-paid subscriber has not enough credit.